


Optimization of solar fields for centrifugal receivers and chemical plants

Presented by Morag Am-Shallem
September 09, 2021



BrightSource

© 2006-2021 BrightSource Energy, Inc. and/or any of its subsidiaries (BrightSource)
The contents of this document and any equipment and/or software described may be protected by trade secrets and patents and patents pending in the People's Republic of China, the United States and/or other countries. This document contains trade secrets and other information that is confidential and proprietary to BrightSource. Any reproduction, disclosure or other use thereof is prohibited except as otherwise agreed to in advance and in writing by BrightSource.





Agenda

- BrightSource Energy
- Optimization of Receiver height and inclination angle
- Solar Field Sizing
- Integration of Solar Field and Chemical Plant



About BrightSource Energy

The Company

- US, UK, Israel, China
- Design, develop & deploy concentrated solar thermal plants
- Sophisticated control
- Internationally renowned technical experience with world-class finance and project development capabilities

The Projects

- **Ivanpah** – 392 MW (3 units)
 - Operating since 2013
 - CA, USA
- **Ashalim** – 121 MW
 - Operating since – 2019
 - Negev, Israel
- **Noor 1** – 100 MW
 - In construction (advanced)
 - Dubai
- **Redstone** – 100 MW
 - In design (financially closed)
 - South Africa



Receiver Configuration – Height and Angle

For the receivers of 2.5 and 5 MWth:

- Checked 3 tower heights: 40m, 60m, 80m,
- Checked 3 receiver inclination angles: 30°, 45°, 60°
- For each configuration:
 - Generate optimal layout
 - Calculate performance of the layout



Receiver Configuration – Height and Angle

For Receiver of 2.5MWth:

- Solar field efficiency at design point (day 81, hour 11.5)

Inclination Angle / Tower Height	30°	45°	60°
40m	0.43	0.39	0.251
60m	0.47	0.44	0.278
80m	0.46	0.43	0.281

- 40m → 60m: Gain ~10%
- 60m → 80m: Loose ~2%
- 30° → 45°: Loose ~8%
- 45° → 60°: Loose ~36%



Receiver Configuration – Height and Angle

For Receiver of 5MWth:

- Solar field efficiency at design point (day 81, hour 11.5)

Inclination Angle / Tower Height	30°	45°	60°
40m	0.46	0.42	0.25
60m	0.53	0.50	0.30
80m	0.55	0.52	0.31

- 40m → 60m: Gain ~16% more
- 60m → 80m: Gain only ~5% more
- 30° → 45°: Loose ~7%
- 45° → 60°: Loose 40%



Solar field Sizing

What is the optimal number of heliostats?

More heliostats in the solar field:

- Increases production

However -


- Higher cost
- The average efficiency of the heliostats decreases
 - Marginal efficiency (of the added heliostats) is small

$$\eta_{rec} = \frac{\text{Power transferred to particles}}{\text{Power incident on receiver aperture}}$$



Solar field Sizing


- Yearly production vs number of heliostats
 - Receiver of 20 MWth





Solar field Sizing


- Average solar field efficiency vs number of heliostats
 - Receiver of 20 MWth





Solar field Sizing

- Production / Total Price
 - Receiver of 20 MWth
- Optimum: ~1500 heliostats (DLR results are similar: 1387)





Solar part vs. Chemical part

- Solar part (Solar Field, Particle Receiver, Cold and Hot particle storage tanks): **Discontinuous operation (Daily startup)**
- Chemical part (sulphuric acid evaporation, SO_3 decomposition, sulphur production via disproportionation, sulphur combustion and combined cycle power generation): **continuous operation**

Challenge: Design the Solar part to be able to provide continuous thermal input to the Chemical part




Solar part vs. Chemical part

Avoid restart of chemical part:


- Day/Night
- Several days without operation

Strategy:


- Design stage:
 - Sizing of the storage and the solar field
- Operation strategy:
 - Reduce load of the chemical plant



Thank you!



BrightSource
Limitless



BrightSource
Limitless

brightsourceenergy.com

